

United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Palent and Trademark Office Address: COMMISSIONUR FOR PATENTS P.O. Box 1950 Alexandry, Virginia 22313-1450

APPLICATION NO.	F.	ILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	ATTORNEY DOCKET NO. CONFIRMATION NO.	
10/045,590	*	11/08/2001	Ian R. Davies	4430-30	8551	
22442	7590	08/28/2006		EXAM	EXAMINER	
SHERIDA		PC	SALL, EL HADJI MALICK			
1560 BROA SUITE 1200				ART UNIT	PAPER NUMBER	
DENVER, CO 80202				2157		
				DATE MAILED: 08/28/200	6	

Please find below and/or attached an Office communication concerning this application or proceeding.

	Application No.	Applicant(s)					
Office Action Occurrence	10/045,590	DAVIES ET AL.					
Office Action Summary	Examiner	Art Unit					
	El Hadji M. Sall	2157					
The MAILING DATE of this communication appears on the cover sheet with the correspondence address Period for Reply							
A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION. - Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication. - Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).							
Status							
1) ■ Responsive to communication(s) filed on 24 Ma 2a) ■ This action is FINAL. 2b) ■ This 3) ■ Since this application is in condition for allowant closed in accordance with the practice under E	action is non-final. ace except for formal matters, pro						
Disposition of Claims							
4) ⊠ Claim(s) 1-42 is/are pending in the application. 4a) Of the above claim(s) is/are withdraw 5) □ Claim(s) is/are allowed. 6) ⊠ Claim(s) 1-42 is/are rejected. 7) □ Claim(s) is/are objected to. 8) □ Claim(s) are subject to restriction and/or							
Application Papers							
 9) The specification is objected to by the Examiner. 10) The drawing(s) filed on is/are: a) accepted or b) objected to by the Examiner. Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a). Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d). 11) The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152. 							
Priority under 35 U.S.C. § 119							
 12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a) All b) Some * c) None of: 1. Certified copies of the priority documents have been received. 2. Certified copies of the priority documents have been received in Application No 3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)). * See the attached detailed Office action for a list of the certified copies not received. 							
Attachment(s) 1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) Paper No(s)/Mail Date 17.0	4)						

1

2.

DETAILED ACTION

This action is responsive to the request for continued examination filed on
 December 12, 2005. Claims 1-42 are pending. Claims 1, 19, 26 and 38 are amended.
 Claims 1-42 represent Obtaining information to facilitate system usage.

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

- (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 3. Claims 1-42 are rejected under 35 U.S.C. 103(a) as being unpatentable over Blumenau et al. (referred to hereafter as Blue) U.S. 6,260,120 in view of Staats et al. U.S. 5,809,331.

Art Unit: 2157

Blue teaches the invention substantially as claimed including storage mapping and partitioning among multiple host processors in the presence of login state changes and host controller replacement (see abstract)

As to claims 1, 19, 26 and 38, Blue teaches methods and apparatuses for facilitating use of a system that includes at least one host and at least one controller, comprising:

Obtaining, by a first storage controller interconnected to said first host by a network, first information for identifying said first host comprising an identity of said at least one host, wherein said first host includes transmitting said first information from said first host to said first storage controller (column 2, lines 55-59, Blue discloses the method further includes receiving at the data port a request for storage access from one of the host processor. The request contains an identification of the host and specification of a portion of the data storage to access; figures 35 and 36); and

Using said first information by said first storage controller in facilitating use of the system, and a list of host having access to data storage through at least said first storage controller (column 2, line 59 to column 3, line 17, Blue discloses the storage controller responds to the request for storage access by decoding the identification, searching the memory to find associated information, and upon finding associated information identifying the host processor; figure 5).

Art Unit: 2157

Blue fails to teach explicitly performing a host computer boot up of a first host, and conducting a bus scan.

However, Staats teaches performing a host computer boot up of a first host, and conducting a bus scan (column 4, lines 53-61, Staats discloses boot information which is accessed during bus initialization; abstract).

It would have been obvious to one of ordinary skill in the art at the time of the invention to modify Blue in view of Staats to provide performing a host computer boot up of a first host, and conducting a bus scan. One would be motivated to do so to allow retrieving the device specific information (abstract).

As to claim 2, Blue teaches the method of claim 1, wherein said bus scan is also conducted for identifying a plurality of different components operatively attached to a bus of said first host (column 10, lines 50-54, Blue discloses the nodes has a number of entities which are identified by logical unit number).

As to claim 3, Blue teaches the method of claim 1, wherein said conducting step does not include activating a programmatic element, on said first host, for obtaining said first information, wherein said programmatic element is able to obtain said first Information without activating a bus scan (column 10, lines 62-67, Blue discloses a host can use a "report LUNs" command to obtain a list of the logical volume to which the host is connected).

Art Unit: 2157

As to claim 4, Blue teaches the method of claim 1, wherein said conducting step includes transmitting said first information, including a world wide name for said first host, to said first storage controller via a fibre channel network (column 9, lines 38-43, Blue discloses in figure 1, the port adapters 35,36 can be programmed to communicate with the network via fibre channel; column 11, lines 14-18, Blue discloses each port of a fibre channel has a world wide name).

As to claim 5, Blue teaches the method of claim 1, wherein said conducting step includes receiving by said first storage controller said first information, including a world wide name for said first host via a communications network (column 9, lines 38-43, Blue discloses in figure 1, the port adapters 35,36 can be programmed to communicate with the network via any number of communication or network protocol).

As to claim 6, Blue teaches the method of claim 1, wherein said using step includes configuring said first storage controller so that said first host has access to said at least one logical storage unit (column 8, lines 24-29, Blue discloses a storage controller for controlling access of the hosts to the storage volumes).

As to claim 7, Blue teaches the method of claim 1, wherein said using step includes providing access to a predetermined data repository, wherein for each of a plurality of host components, said data repository includes corresponding identification data, wherein for at least most of said host components, said corresponding

identification data is accessible independently of whether a host requesting access to said first storage controller includes said host component (column 37, lines 9-16, Blue discloses the host user selects a given storage subsystem adapter port WWN (WWN or World Wide Name is a unique identifier in a Fibre Channel storage network), and all the LUN bitmap entries and their corresponding volume group names are read from the storage subsystem volume configuration database (LUNs or Logical Unit Numbers are addressed in conjunction with the *controller ID* of the host bus adapter, the *target ID* of the storage array, and an optional (and no longer common) *slice ID*)).

As to claim 8, Blue teaches the method of claim 7, wherein said predetermined data portion includes an identification of a manufacturer of a component of said first host (column 37, lines 9-10, Blue discloses a given storage subsystem adaptor port WWN (WWN or World Wide Name is assigned by the vendor at the time of manufacture)).

As to claim 9, Blue discloses the method of claim 8, wherein said component includes a host adapter (column 37, lines 9-10, Blue discloses a subsystem adaptor port).

As to claim 10, Blue discloses the method of claim 1, wherein said step of using includes presenting to an administrator host identifying data indicative of said first information, wherein said presenting of said host identifying data is distinguished from

a presenting of other information for identifying at least a second host so that the administrator can identify said presentation of said host identifying data from said presentation of said other information for said second host by a display attribute that is substantially independent of a content of at least one of said host identifying data and said other information (column 15, lines 16-35, Blue discloses the administrator defines the host names, and the host names are also known to the hosts; column 32, lines 1-5, Blue discloses displaying attribute information such as WWN).

As to claim 11, Blue the method of claim 10, wherein said display attribute includes at least one of: a display order of said presentation of said host identifying data, a display location of said presentation of said host identifying data, and a display highlight or color of said presentation of said host identifying data (column 20, lines 50-61, Blue discloses the volume associated with a particular group could be displayed in a corresponding primary color).

As to claim 12, Blue teaches the method of claim 11, wherein said display order includes providing said presentation of said host identifying data before said presentation of said other information (column 30, lines 57-59, Blue discloses the display starts out with a list of storage subsystems and a list of hosts linked by the data network).

As to claim 13, Blue teaches the method of claim 1, wherein said step of using includes:

Presenting, to an administrator of said first storage controller, host identifying data indicative of said first information (column 24, lines 60-67, Blue discloses the administrator assigned the virtual ports to the host, and the host must use this information to direct their storage access to the virtual ports);

Receiving input from the administrator of separate information for identifying said first host (column 24, lines 60-67, Blue discloses the port assignment by the administrator (i.e. for identifying the hosts)); and

at least one of: (a) displaying said separate information with at least a portion of said host identifying data and (b) displaying said separate information in place of at least a portion of said host identifying data (column 32, lines 1-5, Blue discloses displaying attribute information such as port WWN).

As to claim 14, Blue teaches the method of claim 13, wherein said separate information assists the administrator in identifying said first host (column 26, lines 34-36, Blue discloses separate tables are used because each host listed in the host table can have more than one assigned port (it is inherent that the administrator is assigning the port using the information in the tables)).

As to claim 15, Blue teaches the method of claim 13, wherein a presentation of said separate information includes at least one of: textual data representing said separate information, a hyperlink for said separate information, and a menu for activating one or more tasks related to managing said logical storage units (column 36, line 66 - column 37, line 6, Blue discloses the host installation facility reads the storage subsystem port text names. If the port entries are zero, it means they have never been entered).

As to claim 16, Blue teaches the method of claim 13, further including:
using, by the administrator, said separate information for at least one of:
assigning, designing and changing access permissions to one or more logical storage
units available to said first host (column 32, lines 25-33, Blue discloses additional
facilities could be introduced for volume configuration and site management to permit
involvement of the host in allocating logical storage volumes).

As to claim 17, Blue teaches a method of claim 1, wherein data storage is part of the system (figure 1, item 20).

As to claim 18, Blue teaches the method of claim 1, further including a step of obtaining a timestamp of when said first storage controller obtains said first information, wherein data indicative of said timestamp is available for presentation to an administrator of said first controller (column 39, lines 44-54, Blue discloses the time

that a host controller is logged in to a port adaptor (by logging into the a port adaptor information or/and data is implicitly "presented to an administrator)).

As to claim 20, Blue teaches the method of claim 19, wherein said using step includes determining whether said first information is: available via said network switch without accessing said first host, and includes at least one predetermined data portion for identifying said first host (column 25, lines 30-33, Blue discloses requests from other nodes in the network are routed to them through their respective virtual switches).

As to claim 21, Blue teaches the method of claim 19, wherein said accessing step includes querying said network switch for said first information, wherein said first information includes at least one of: a network address for said first host and a network communications protocol used by said first host (column 32, lines 12-14, Blue teaches the storage subsystem can assign network addresses to virtual ports).

As to claim 22, Blue teaches the method of claim 19, wherein said network switch is a storage area network switch that includes a fibre channel switch (figure 21).

As to claim 23, Blue teaches the method of claim 22, wherein said querying step includes providing a world wide name for said first host to a database interface component of said fibre channel switch, wherein said world wide name is used for

Art Unit: 2157

retrieving said first information (column 25, lines 28-49, Blue discloses the ports are assigned WWNs, the switch definition include the respective WWNs of the virtual switches, and the name servers can provide the respective WWNs (by having the WWNs, it is inherent it could be used to "retrieve information)).

As to claim 24, Blue teaches the method of claim 19, wherein said accessing step includes:

registering said first storage controller with said network switch (column 25, lines 21-23, Blue discloses there is a switch 238, 239 in the storage controller); and subsequent to completion of said registering step, receiving, by said first controller, information related to said network switch that is being contacted by one or more hosts for requesting access to said first storage controller (figure 21; column 2, lines 55-57, Blue discloses receiving request for storage access).

As to claim 25, Blue teaches the method of claim 19, wherein said using step includes determining whether access to at least one of a plurality of logical storage units for said first host is to be granted (figure 33).

As to claim 27, Blue teaches the apparatus of claim 23, wherein said storage controller accesses a network switch, via a transmission on a network, for obtaining second information for identifying the first host, wherein said transmission is provided to the network by said network interface (figure 21).

Art Unit: 2157

As to claim 28, Blue teaches the apparatus of claim 27, wherein one or more of:

(a) said first information includes a world wide name for the first host (column 9, lines 38-43, Blue discloses in figure 1, the port adapters 35,36 can be programmed to communicate with the network via fibre channel; column 11, lines 14-18, Blue discloses each port of a fibre channel has a world wide name); and

Page 12

(b) said second information includes one or more of: an identification of a manufacturer of a component of the first host, a network address for the first host, a network communications protocol being used by the first host, and a make or model of a component of the first host (column 37, lines 9-10, Blue discloses a given storage subsystem adaptor port WWN (WWN or World Wide Name is assigned by the vendor at the time of manufacture)).

As to claim 29, Blue teaches the apparatus of claim 26, wherein said administration subsystem includes a host identification processing subsystem for presenting said first host identifying data to an administrator for said apparatus, wherein said presentation of said first host identifying data is distinguished from a presentation of other information for identifying at least a second host so that the administrator can identify said presentation of said first host identifying data from said presentation of said other information for the second host using a display attribute (column 15, lines 16-35, Blue discloses the administrator defines the host

names, and the host names are also known to the hosts; column 32, lines 1-5, Blue discloses displaying attribute information such as WWN).

As to claim 30, Blue teaches the apparatus of claim 29, wherein said storage controller is accessed by the first host more recently than being accessed by the second host (column 2, lines 46-49, Blue discloses the storage controller has at least one data port to connect to the data network (It is inherent that first host in the plurality of hosts could access "more recently" the controller than any second host)).

As to claim 31, Blue teaches the apparatus of claim 29, wherein said display attribute is substantially independent of content of said first host identifying data (column 20, lines 50-61, Blue discloses the volume associated with a particular group could be displayed in a corresponding primary color).

As to claim 32, Blue teaches the apparatus of claim 29, wherein said display attribute includes at least one of: a display order of said presentation of said first host identifying data, a display location of said presentation of said first host identifying data, and a display highlighting or color of said presentation of said first host identifying data (column 20, lines 50-61, Blue discloses the volume associated with a particular group could be displayed in a corresponding primary color).

Art Unit: 2157

As to claim 33, Blue teaches the apparatus of claim 32, wherein said display order includes providing said presentation of said first information before said presentation of said other information (column 30, lines 57-59, Blue discloses the display starts out with a list of storage subsystems and a list of hosts linked by the data network).

As to claim 34, Blue teaches the apparatus of claim 26, wherein said administration subsystem includes a host identification processing subsystem for:

- (a) presenting, to an administrator of said apparatus, via a display device, said first host identifying data (column 24, lines 60-67, Blue discloses the port assignment by the administrator (i.e. for identifying the hosts);
- (b) receiving input, from the administrator, of third information for identifying the first host (column 24, lines 60-67, Blue discloses the port assignment by the administrator (i.e. for identifying the hosts); and
- (c) at least one of: (a) displaying said third information, via the display device, with at least a portion of said first host identifying data, (b) displaying said third information, via the display device, in place of at least a portion of said first host identifying data, and (c) using, by the administrator, said third information for one or more of: assigning, designing and changing access permissions to one or more logical storage units to the first host (column 32, lines 25-33, Blue discloses additional facilities could be introduced for volume configuration and site management to permit involvement of the host in allocating logical storage volumes).

As to claim 35, Blue teaches the apparatus of claim 34, wherein a presentation of said third information, via the display device, includes at least one of: textual data representing said third information, a hyperlink for said third information, and a menu for activating one or more tasks related to managing said logical storage units (column 36, line 66 - column 37, line 6, Blue discloses the host installation facility reads the storage subsystem port text names. If the port entries are zero, it means they have never been entered).

As to claim 36, Blue teaches the apparatus of claim 26, wherein said storage controller accesses a data repository including identification data for identifying at least one component of the first host, and said identification data is accessible from said data repository independently of a request for access to said controller by the first host (column 37, lines 9-16, Blue discloses the host user selects a given storage subsystem adapter port WWN (WWN or World Wide Name is a unique identifier in a Fibre Channel storage network), and all the LUN bitmap entries and their corresponding volume group names are read from the storage subsystem volume configuration database (LUNs or Logical Unit Numbers are addressed in conjunction with the *controller ID* of the host bus adapter, the *target ID* of the storage array, and an optional (and no longer common) *slice ID*)).

As to claim 37, Blue teaches the apparatus of claim 26, further including a data store for storing data that includes at least a first data storage portion having an identifier known to at least the first host when the first host has access to said first data storage portion (figure 1, item 20).

As to claim 39, Blue teaches the apparatus of claim 38, wherein said storage controller determines, for at least the first host, second information for identifying the first host from a bus scan on the first host (column 2, lines 63-65, Blue discloses searching to find information identifying the host processor (i.e. bus scan for obtaining information identifying the first host)).

As to claim 40, Blue teaches the apparatus of claim 39, wherein said first information includes one or more of: an identification of a manufacturer of a component of the first host, a network address for the first host, a network communications protocol being used by the first host, and a make or model of a component of the first host and said second information includes a world wide name for the first host (column 37, lines 9-10, Blue discloses a given storage subsystem adaptor port WWN (WWN or World Wide Name is assigned by the vendor at the time of manufacture)).

As to claim 41, Blue teaches the apparatus of claim 39, wherein said administration subsystem presents first host identifying data indicative of said second information that is distinguished from a presentation of other information for identifying

Application/Control Number: 10/045,590 Page 17

Art Unit: 2157

4.

at least a second host using a display attribute (column 15, lines 16-35, Blue discloses the administrator defines the host names, and the host names are also known to the hosts; column 32, lines 1-5, Blue discloses displaying attribute information such as WWN).

As to claim 42, Blue teaches the apparatus of claim 41, wherein said display attribute includes at least one of: a display order related to said first host identifying data, a display location related to said first host identifying data and a display highlighting or color related to said first host identifying data (column 20, lines 50-61, Blue discloses the volume associated with a particular group could be displayed in a corresponding primary color).

Response to Arguments

Applicant's arguments filed 05/24/06 have been fully considered but they are not persuasive.

(A) Applicant argues that the cited references do not teach, suggest or disclose using a host bus scan to distribute information identifying the host to other devices.

In regards to point (A), examiner respectfully disagrees.

Art Unit: 2157

In column 2, lines 55-59, Blue discloses the method further includes receiving at the data port a request for storage access from one of the host processor. The request contains an identification of the host and specification of a portion of the data storage to access. This portion of Blue explicitly teaches "distribute information identifying the host to other devices". However, in column 4, lines 53-61, Staats discloses boot information which is accessed during bus initialization; and in the abstract, Staats teaches upon system initialization, the bus is scanned and device-specific identification information is retrieved from command and status configuration ROMs associated with each of the plurality of nodes. It would have been obvious to one of ordinary skill in the art at the time of the invention to modify Blue in view of Staats to provide performing a host computer boot up of a first host, and conducting a bus scan. One would be motivated to do so to allow retrieving the device specific information (abstract).

Page 18

(B) Applicant argues that there is no discussion in Blue of a storage controller that obtains information identifying a host from a bus scan conducted by that host. That is, Blue does not discuss a system in which a storage controller or other device obtains information identifying a host performing a network scan initiated by the host from the network scan.

In regards to point (B), examiner respectfully disagrees.

The above arguments were addressed in point (A).

(C) Applicant argues that Blue does not describe a system in which the WWN or other information related to a host is provided to a storages system controller through a bus scan performed by the host.

Page 19

In regards to point (C), examiner respectfully disagrees.

Limitation such as "a system in which the WWN or other information related to a host is provided to a storages system controller through a bus scan performed by the host" is not in the claims.

(B) Applicant argues that there is no discussion in Staats of using a host bus scan to distribute information identifying the host.

In regards to point (B), examiner respectfully disagrees.

The above arguments were addressed in point (A).

5. Conclusion

THIS ACTION IS MADE FINAL. Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the

Application/Control Number: 10/045,590 Page 20

Art Unit: 2157

shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to El Hadji M Sall whose telephone number is 571-272-4010. The examiner can normally be reached on 8:00-4:30.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Ario Etienne can be reached on 571-272-4001. The fax phone number for the organization where this application or proceeding is assigned is 571-273-4010.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

El Hadji Sall

Patent Examiner

Art Unit: 2157

ARIO ETIENNE
SUPERVISORY PATENT EXAMINER
TECHNOLOGY CENTER 2100